

## CLAIMS

What is claimed is:

- 9/3/17
1. (Currently amended) A method for controlling the update frequency of a positioning device in a mobile terminal, said method comprising:
- storing at least one reference position indicative of a remote location of interest in said mobile terminal;
  - determining the current position of said mobile terminal;
  - computing a distance of said current position of said mobile terminal from said reference position; and
  - determining a position update frequency based on said distance between said current position of said mobile terminal and said ~~reference~~ reference position.
2. (Original) The method of claim 1 wherein determining a position update frequency based on said distance between said current position of said mobile terminal and said reference position comprises increasing said update frequency as said distance between said current position of said mobile terminal and said reference position decreases.
3. (Original) The method of claim 1 wherein determining a position update frequency based on said distance between said current position of said mobile terminal and said reference position comprises decreasing said update frequency as said distance between said current position of said mobile terminal and said reference position increases.
4. (Original) The method of claim 1 further comprising determining the velocity of said mobile terminal based on two or more position estimates.

5. (Currently amended) The method of claim 4 wherein determining said position update frequency as a function of said distance between said current position of said mobile terminal and said reference position further comprises determining said position update frequency as a function of said distance between said current position and said reference position and said velocity of said mobile terminal.

6. (Original) The method of claim 5 wherein determining said position update frequency as a function of said distance between said current position of said mobile terminal and said reference position and said velocity of said mobile terminal comprises increasing said position update frequency as said velocity increases and decreasing said position update frequency as said velocity decreases.

7. (Original) The method of claim 1 further comprising:

comparing said distance between said current position of said mobile terminal and said reference position to a predetermined threshold; and

performing a predetermined action if said distance between said current position of said mobile terminal and said reference position meets said threshold.

8. (Original) The method of claim 7 wherein performing a predetermined action if said distance between said current position of said mobile terminal and said reference position meets said threshold comprises searching for a channel in an alternate network.

9. (Currently amended) The method of claim 8 wherein searching for a channel in an alternate network comprises searching for a control channel in a private wireless telephone system.

10. (Currently amended) A mobile terminal comprising:

a transceiver transmitting and receiving signals over a wireless channel;  
memory storing at least one reference position indicative of a remote location of interest;  
a position estimator to periodically determine a current position of said mobile terminal at  
a variable position update frequency; and  
control logic including a processor to calculate the distance of said mobile terminal from  
said reference position based on said current position of said mobile terminal and  
to adjust said variable position update frequency as a function of said distance of  
said mobile terminal from said reference position.

11. (Original) The mobile terminal of claim 10 wherein said position estimator is in a removable  
device removably attached to said mobile terminal.

12. (Original) The mobile terminal of claim 10 wherein said position estimator comprises a GPS  
receiver.

13. (Original) A method of initiating a search for a control channel in a communications network  
by a mobile terminal, said method comprising:

storing at least one reference position indicative of the location of said communications  
network in said mobile terminal;  
determining the current position of said mobile terminal;  
computing the distance of said current position of said mobile terminal from said  
reference position; and  
initiating a search for a channel based on said distance between said mobile terminal  
and said communication network.

14. (Original) The method of claim 13, including establishing communication between said and said mobile terminal and said communication network.

15. (Original) The method of claim of claim 14 wherein establishing communications between said mobile terminal and said communications network comprises establishing communication with a private radiocommunication system.

16. (Original) The method of claim 15 wherein establishing communication with a private radiocommunication system comprises establishing communication with said private radiocommunication system via a short-range air interfere.

a1 17. (Original) The method of claim 16 wherein establishing communication with said private radiocommunication system via a short-range air interfere comprises establishing communication with said private radiocommunication system via a Bluetooth interface.

18. (Original) The method of claim 13, wherein determining the current position of said mobile terminal comprises receiving signals from navigation satellites and calculating said current position from said signals received from said navigation satellites.

19. (Original) The method of claim 13, wherein determining said current position of said mobile terminal is repeated at intervals dependant on said distance of said current position of said mobile terminal from said reference position.

20. (Original) The method of claim 13, further comprising determining the rate of change in said position of said mobile terminal relative to said reference position.

21. (Original) The method of claim 20, wherein determining said current position of said mobile terminal is repeated at intervals dependant on said rate of change of distance of said mobile terminal from said reference position.

22. (Original) The method of claim 20, including determining the rate of change in said position of said mobile terminal relative to said reference position and initiating a search for a channel when: (i) said distance between the mobile terminal and the reference position is less than said predetermined distance, and, (ii) said rate of change in said position of said mobile terminal relative to said reference position exceeds a predetermined value.

23. (Original) A mobile terminal comprising:

a transceiver transmitting and receiving signals over a wireless channel;  
memory storing at least one reference position indicative of the location of a communications network;  
a position estimator to determine a current position of said mobile terminal; and  
control logic including a processor to calculate the distance of said mobile terminal from said reference position based on said current position of said mobile terminal and to initiate a search for a channel based on said calculated distance.

24. (Original) The mobile terminal of claim 23, wherein said position estimator comprises a receiver adapted to receive signals from navigation satellites and to calculate said current position from said received signals.

25. (Original) The mobile terminal of claim 23, wherein said control logic further calculates the rate of change of said current position relative to said reference position.

26. (Original) The mobile terminal of claim 25, wherein said control logic updates said current position at a frequency dependant on said rate of change of said current position relative to said reference position.

27. (Original) The mobile terminal of claim 23, wherein said control logic further calculates the rate of change of said current position of said mobile terminal relative to said reference position, and initiates a search for a channel based on said calculated distance between said mobile terminal and said reference position and said rate of change of said current position of said mobile terminal relative to said reference position.

al

28. (Original) The mobile terminal of claim 23 wherein said mobile terminal further comprises a Bluetooth interface.

29. (Original) A method for controlling the initiation of searches by a mobile terminal for a channel associated with a private radiocommunication system, said method comprising:

- storing a reference position within the mobile terminal, said reference position being within the boundaries of the private radiocommunication system;
- determining the current position of said mobile terminal;
- computing the distance of said current position of said mobile terminal from said reference position; and
- initiating a search for a channel provided by said private radiocommunication system based on said computed distance between said current position of said mobile terminal and said reference position.

30. (Currently amended) The method of claim 29, wherein determining the current position of said mobile terminal and computing the distance of said current position of said mobile terminal from said reference position are ~~performed~~ performed repeatedly.

31. (Currently amended) The method of claim 29, wherein said mobile terminal repeatedly searches for a channel provided by said private radiocommunication system as long as said distance of said current position of said mobile terminal from said reference position is less than ~~said a~~ predetermined distance.

21

32. (Currently amended) The method of claim 29, further including determining the rate of change of said distance between said current position of said mobile terminal and said reference position and initiating a search for a channel provided by said private radiocommunication system in response to: (i) said rate of change being greater than a predetermined value, and, (ii) said distance between said current position of said mobile terminal and said reference position being less than a predetermined distance.

33. (Original) The method of claim 29, wherein initiating a search for a channel provided by said private radiocommunication system is further based on the rate of change of said distance between said current position of said mobile terminal and said reference position.

34. (Original) A method of controlling the initiation of a search by a mobile terminal for a channel associated with a radiocommunication system comprising:

repeatedly determining the location of the mobile terminal with respect to a reference position associated with the radio communication system; and

initiating a search for a channel associated with said radio communication system if the computed distance between the mobile terminal and the reference position is less than a predetermined distance.

35. (Original) The method of claim 34 further comprising:

repeatedly determining the rate of change of said distance between said mobile terminal and said reference position; and

initiating a search for the channel associated with said radio communication system when:

- (i) the distance between said mobile terminal and said reference position is less than said predetermined distance, and,
- (ii) (ii) when the rate of change of the distance between said mobile terminal and said reference position exceeds a predetermined value.